




MEMS Packaging

Innovative Adhesives
and Solutions



Microelectromechanical system



Cutting-edge adhesives for MEMS packaging

Unique: High flexibility combined with high die shear strength

Microelectromechanical systems (MEMS) are found in many everyday products. These tiny components are used in many fields of applications. In particular, mobile phones contain numerous MEMS elements: Microphones for voice recognition and noise suppression, gyroscopes and accelerometers for position detection and orientation verification, pressure sensors for indoor navigation, and many more.

Also, automotive applications cannot be engineered without MEMS anymore. They are used as pressure

sensors for tire pressure monitoring (TPMS), oil pressure sensors in the gear, and acceleration sensors in airbags. Adhesives for MEMS packaging must master special challenges. Especially when bonding the MEMS chip to the substrate, high flexibility of the adhesive is required. DELO's highly flexible adhesives compensate tensions during temperature changes as a consequence of dissimilar coefficients of expansion (thermal mismatch). This provides for stable signal characteristics! Despite this high flexibility, the special MEMS adhesives give outstanding die shear strength.

We have the adhesives you need!

You insist on the best performance?

- DELO's adhesives provide a unique property combination of highest flexibility and die shear strength

You expect efficient processes with short process times?

- DELO's adhesives enable fast processes thanks to extremely short curing times.


You demand the utmost reliability for your MEMS applications?

- DELO's adhesives give excellent resistance when exposed to thermal stress and humidity, and stand out by unchanged material properties without embrittlement.

DELO – best performance for MEMS packaging




Watch the animation at www.youtube.com/DELOadhesives




1 MEMS die attach

- High flexibility (Young's modulus: 5 MPa) in combination with high die shear strength
- Steady flexibility upon continuous thermal stress up to +120 °C
- Short process time at low curing temperature: 15 min @ +100 °C



2 Cap bonding

- Very high impact resistance
- Excellent adhesion to Au, Ni and stainless steel
- Short process time: 5 min @ +130 °C
- High electrical conductivity (shielding)



3 Glob top

- High flexibility
- Jettable
- Short process time at low curing temperature: 15 min @ +100 °C

4 ASIC die attach

- Curing within just seconds
- Low curing temperature of +80 °C
- High reliability



CONTACT

Headquarters

DELO Industrial Adhesives

- **Germany** · Windach/Munich
Phone +49 8193 9900-0
info@DELO.de
www.DELO.de

DELO Industrial Adhesives

- **USA** · Sudbury/Boston, MA
Phone +1 978 254 5275
usa@DELO-adhesives.com
www.DELO-adhesives.com/us

DELO Industrial Adhesives

- **Singapore**
Phone +65 6807 0800
singapore@DELO-adhesives.com
www.DELO-adhesives.com/en

DELO Industrial Adhesives

- **China** · Shanghai
Phone +86 21 2898 6569
china@DELO-adhesives.com
www.DELO-adhesives.com/cn

DELO Industrial Adhesives

- **Taiwan** · Taipei
Phone +886 2 6639 8248
taiwan@DELO-adhesives.com
www.DELO-adhesives.com/cn

DELO Industrial Adhesives

- **Malaysia** · Kuala Lumpur
Phone +65 6807 0800
malaysia@DELO-adhesives.com
www.DELO-adhesives.com/en

DELO Industrial Adhesives

- **South Korea** · Seoul
Phone +82 2 2190 3727
korea@DELO-adhesives.com
www.DELO-adhesives.com/en

The data and information provided are based on tests performed under laboratory conditions. Reliable information about the behavior of the product under practical conditions and its suitability for a specific purpose cannot be concluded from this. It is the user's responsibility to test the suitability of the product for the intended purpose by considering all specific requirements. Type, physical and chemical properties of the materials to be processed with the product, as well as all actual influences occurring during transport, storage, processing and use, may cause deviations in the behavior of the product compared to its behavior under laboratory conditions. All data provided are typical average values or uniquely determined parameters measured under laboratory conditions. The data and information provided are therefore no guarantee for specific product properties or the suitability of the product for a specific purpose. Nothing contained herein shall be construed to indicate the non-existence of any relevant patents or to constitute a permission, encouragement or recommendation to practice any development covered by any patents, without permission of the owner of this patent. All products provided by DELO are subject to DELO's General Terms of Business. Verbal ancillary agreements are deemed not to exist.

© DELO – This brochure including any and all parts is protected by copyright. Any use not expressly permitted by the Urheberrechtsgesetz (German Copyright Act) shall require DELO's written consent. This shall apply without limitation to reproductions, duplications, disseminations, adaptations, translations and microfilms as well as to the recording, processing, duplication and/or dissemination by electronic means.

04/16

Adhesives

Dispensing

Curing

Consulting

DELO